

PRO range

TITAN | 15

TYPE PRO

For large scale operators requiring a high specification on highways and in the field.


Standard equipment

Boron Steel Beaters | Rear Slurry Door | Flashing Beacon
Wide Angle PTO with Cam Clutch | 580/70 R38 Wheels and Tyres | Commercial Axle with Air/Hydraulic Brakes

Optional equipment

Side Extensions | Electronic Bed Speed Control | LED Strobe Light | Compost/Poultry/Manure Beater Tips
ISOBUS Weigh Cell System | Sprung Drawbar | 650/65 R38 Wheels & Tyres | Ball Hitch (80mm) for Sprung Drawbar



									
	A = Overall Height (ft)	B = Overall Width (ft)	C = Loading Height (ft)	D = Overall Length (ft)	Capacity (with extensions ft ³)	Power min	Weight	Tyres	PTO rpm
TITAN 15	11' 9"	9' 6" *	8' 3" *	26'	543 ft ³ (634 ft ³)	150	13,845 lbs	580/70 R38	1000

TITAN | 17

TYPE PRO

Catering to the needs of large-scale operators seeking exceptional specifications for both highway and field operations.


Standard equipment

Boron Steel Beaters | Rear Slurry Door | Flashing Beacon
Wide Angle PTO with Cam Clutch | 580/70 R38 Wheels and Tyres | Commercial Axle with Air/Hydraulic Brakes

Optional equipment

Side Extensions | Electronic Bed Speed Control | LED Strobe Light | Compost/Poultry/Manure Beater Tips
ISOBUS Weigh Cell System | Sprung Drawbar | 650/65 R38 Wheels & Tyres | Ball Hitch (80mm) for Sprung Drawbar



									
	A = Overall Height (ft)	B = Overall Width (ft)	C = Loading Height (ft)	D = Overall Length (ft)	Capacity (with extensions ft ³)	Power min	Weight	Tyres	PTO rpm
TITAN 17	11' 9"	9' 6" *	8' 3" *	27' 11"	604 ft ³ (710 ft ³)	170	14,462 lbs	580/70 R38	1000